



Photographic Solutions

Safety Data Sheet

PEC-12[®]

SDS Revision Date: 01/01/2024

1. Identification

1.1 Product identifier

Product Identity: PEC-12[®]
Alternate Names: none

1.2 Relevant identified uses of the substance or mixture and uses advised against

Intended use: PEC-12[®] is intended for removing non-water based stains, markings and debris from conventional silver based photographic emulsions (films and/or prints whether in color or B&W). It is best to spray a few drops onto a soft lint free applicator and then wipe the moistened applicator lightly over the area to be cleaned.

Application Method: See Technical Data Sheet

1.3 Details of the supplier of the data sheet

Company Name: Photosol, Inc. dba Photographic Solutions
6010 New Utrecht Ave Brooklyn, NY USA

Emergency: **CHEMTREC** (CCN17280) **USA:** (800) 424-9300 **International:** +1 (703) 527-3887
Customer Service: **Photosol, Inc. dba Photographic Solutions** Phone (929) 562-1730

2. Hazard(s) Identification

2.1 Classification of the substance or mixture

Flam. Liq 3: H226 Flammable liquid and vapor
STOT SE 3: H336 May cause drowsiness or dizziness

2.2 Label Elements

Using the Toxicity Data listed in sections 11 and 12 the product is labeled as follows.



H226 Flammable liquid and vapor.
H336 May cause drowsiness and dizziness.

[Prevention]:

P210 Keep away from heat / sparks / open flame / hot surfaces – No smoking.
P235 Keep cool.
P240 Ground / bond container and receiving equipment.
P241 Use explosion-proof electrical / ventilating / light / equipment.
P242 Use only non-sparkling tools.
P243 Take precautionary measures against static discharge.
P261 Avoid breathing dust / fume / gas / mist / vapors / spray.
P280 Wear protective gloves / eye protection / face protection.



Photographic Solutions

Safety Data Sheet

PEC-12[®]

SDS Revision Date: 01/01/2024

[Response]:

P303+361+353 IF ON SKIN (or hair): Remove / Take off immediately all contaminated clothing. Rinse skin with water / shower.
P304+312 IF INHALED: Call a POISON CENTER or doctor / physician if you feel unwell.
P340: Remove victim to fresh air and keep at rest in a position comfortable for breathing.
P370+378 In case of fire: Use extinguishing media listed in section 5 of SDS for extinction.

[Storage]:

P403+233 Store in a well-ventilated place. Keep container tightly closed.
P405 Store locked up.

[Disposal]:

P501 Dispose of contents / container in accordance with local / national regulations.

3. Composition/Information on Ingredients

This product contains the following substance that present a hazard within the meaning of the relevant State and Federal Hazardous Substances regulations.

Ingredient/Chemical Designation	Weight %	GHS Classification	Note
Ethanol CAS Number: 0000064-17-5	75-100	Flam. Liq. 2;H225	[1][2]
N-Butyl Acetate CAS Number: 0000123-86-4	10-25	Flam. Liq. 3;H226 STOT SE 3;H336	[1][2]

In accordance with paragraph (i) of §1910.1200, the specific chemical identity and/or exact percentage (concentration) of composition has been withheld as a trade secret.

[1] Substance classified with a health or environmental hazard.

[2] Substance with a workplace exposure limit

[3] PBT-substance or vPvB-substance.

The full texts of the phrases are shown in Section 16.

4. First Aid Measures

4.1 Description of first aid measures

General	In all cases of doubt, or when symptoms persist, seek medical attention. Never give anything by mouth to an unconscious person.
Inhalation	Remove to fresh air, keep patient warm and at rest. If breathing is irregular or stopped, give artificial respiration. If unconscious place in the recovery position and obtain immediate medical attention. Give nothing by mouth.
Eyes	Irrigate copiously with clean water for at least 15 minutes, holding the eyelids apart and seek medical attention.
Skin	Remove contaminated clothing. Wash skin thoroughly with soap and water or use a recognized skin cleanser.
Ingestion	If swallowed obtain immediate medical attention. Keep at rest. Do NOT induce vomiting.



Photographic Solutions

Safety Data Sheet

PEC-12[®]

SDS Revision Date: 01/01/2024

4.2 Most important symptoms and effects, both acute and delayed

Overview

Causes Eye Irritation

Ingestion may cause blindness.

Avoid prolonged breathing of vapors as it may cause dizziness, nausea and/or headache.

Avoid prolonged and/or repeated skin contact as it may cause drying, cracking and/or irritation.

Exposure to solvent vapor concentrations from the component solvents in excess of the stated occupational exposure limits may result in adverse health effects such as mucous membrane and respiratory system irritation and adverse effects on the kidneys, liver and central nervous system. Symptoms include headache, nausea, dizziness, fatigue, muscular weakness, drowsiness and in extreme cases, loss of consciousness.

Repeated or prolonged contact with the preparation may cause removal of natural fat from the skin resulting in dryness, irritation and possible non-allergic contact dermatitis. Solvents may also be absorbed through the skin. Splashes of liquid in the eyes may cause irritation and soreness with possible reversible damage.

See section 2 for further details.

Inhalation

May cause drowsiness or dizziness.

5. Fire-Fighting Measures

5.1 Extinguishing media

Use a dry carbon dioxide (CO₂), or foam. Keep fire exposed containers cool with a water spray.

Water may be ineffective in fire-fighting.

5.2 Special hazards arising from the substance or mixture

Hazardous decomposition: Carbon dioxide, Carbon monoxide

Keep away from heat / sparks / open flames / hot surfaces – No smoking.

Keep cool ground / bond container and receiving equipment.

Use explosion-proof electrical / ventilating / light / equipment.

Use only non-sparkling tools.

Take precautionary measures against static discharge.

Avoid breathing dust / fume / gas / mist / vapors / spray.

5.3 Advise for fire-fighters

Wear self-contained breathing apparatus and protective clothing.

Vapors may travel a considerable distance causing a flash fire or flashback.

None

ERG Guide No. 128

6. Accidental Release Measure

6.1 Personal precautions, protective equipment and emergency procedures

Put on appropriate personal protective equipment (see section 8).

6.2 Environmental precautions

Do not allow spills to enter drains or waterways.

Use good personal hygiene practices. Wash hands before eating, drinking, smoking or using toilet.

Promptly remove soiled clothing and thoroughly before reuse.

Collect in flammable waste container for disposal.



Photographic Solutions

Safety Data Sheet

PEC-12[®]

SDS Revision Date: 01/01/2024

6.3 Methods and material for containment and cleaning up

Procedures to be used in case of leak/spill: Eliminate all ignition sources.
 Assure adequate ventilation and/or respirators for clean-up personnel.
 For large spills use water spray to disperse vapors and flush spill area.
 Prevent runoff from entering drains, sewers and streams.
 Wipe smaller spills with untreated clean cloths, wipes or vermiculite.
 Dispose of same by incineration
 Waste Disposal: Dispose of minute excess by placing container outdoors and allow to evaporate.

7. Handling and Storage

7.1 Precautions for safe handling

Product should be sprayed into a cloth or swab (the applicator) by lightly and partially depressing sprayer. Applicator should be touching sprayer when spraying as this will eliminate a large percentage of product from becoming airborne and significantly reduce wasting product. When used as directed and intended, this product does not require special handling procedures, HOWEVER, when product is in constant or repeated use, adequate ventilation must be provided, and protective gloves should be worn. Because PEC-12 is designed to remove skin oils from film/prints, persons with chronically dry or sensitive skin, eczema, etc. should wear gloves regardless of frequency of handling.
 See section 2 for further details. – [Prevention]:

7.2 Conditions for safe storage, including any incompatibilities

Handle containers carefully to prevent damage and spillage.
 Naked flames and smoking should not be permitted in storage areas.
 It is recommended that fork lift trucks and electrical equipment are protected to the appropriate standard.
 Incompatible materials:
 CBI#1: This ingredient is incompatible and causes violent reactions or ignitions with the following substances: Acetylene Bromide, Platinum, Potassium tert-butoxide, Phosphorus III oxide, Sodium, and Disulfuryl DiFluoride (violent reaction when mixed at ambient temperatures).
 CBI#2: This ingredient is incompatible with Potassium tert-butoxide
 Store away from heat and/or ignition sources, open flames, etc.
 For added safety, a storage cabinet specifically designed for flammable liquids should be utilized.
 See section 2 for further details. – [Storage]:

7.3 Specific end use(s)

No data available

8. Exposure Controls and Personal Protection

8.1 Control Parameters

Exposure

CAS No.	Ingredient	Source	Value
0000064-17-5	Ethanol	OSHA	TWA 1000 ppm (1900 mg/m ³)
		ACGIH	STEL: 1000 ppm Revised 2009,
		NIOSH	TWA 1000 ppm (1900 mg/m ³)
		Supplier	No Established Limit
0000123-86-4	N-Butyl Acetate	OSHA	TWA 150 ppm (710 mg/m ³)
		ACGIH	TWA: 20 ppm
		NIOSH	TWA 150 ppm (710 mg/m ³) ST 200 ppm (950 mg/m ³)
		Supplier	No Established Limit



Photographic Solutions

Safety Data Sheet

PEC-12®

SDS Revision Date: 01/01/2024

Carcinogen Data

CAS No.	Ingredient	Source	Value
0000064-17-5	Ethanol	OSHA NTP IARC	Select Carcinogen: No Known: No; Suspected: No Group 1: Yes; Group 2a: No; Group 2b: No; Group 3: No; Group 4: No;
0000123-86-4	N-Butyl Acetate	OSHA NTP IARC	Select Carcinogen: No Known: No; Suspected: No Group 1: No; Group 2a: No; Group 2b: No; Group 3: No; Group 4: No;

8.2 Exposure Controls

Respiratory	A respirator for organic solvents should be used if airborne cannot be maintained below recommended limits (12 air changes per hour or 850ppm).
Eyes	Safety goggles or safety glasses with side shields.
Skin	Gloves should be worn for prolonged or repeated contact. A high-quality plastic examination glove should be adequate. Use neoprene or rubber gloves or PVC.
Engineering Controls	Provide adequate ventilation. Where reasonably practicable this should be achieved by the use of local exhaust ventilation and good general extraction. If these are not sufficient to maintain concentrations of particulates and any vapor below occupational exposure limits suitable respiratory protection must be worn.
Other Work Practices	Use good personal hygiene practices. Wash hands before eating, drinking, smoking or using toilet. Promptly remove soiled clothing and wash thoroughly before reuse.

See Section 2 for further details. – [Prevention]:

9. Physical and Chemical Properties

9.1 Physical and Chemical Properties

Appearance	Colorless Liquid
Odor	Fruity
Odor threshold	850 Not Measured
pH	7.0
Melting point / freezing point	+/- (-100°F)
Initial boiling point and boiling range	165°F
Flash Point	75°F using Tag Closed Cup method
Evaporation rate (Ether = 1)	>1 (Butyl Acetate=1)
Flammability (solid, gas)	Not Applicable
Upper/lower flammability or explosive limits	Lower Explosive Limit: 2% volume in air STP Upper Explosive Limit: 15% volume in air STP
Vapor pressure (Pa)	43.2 mmHg at 68°F
Vapor Density	>1 (Air=1)
Specific Gravity	0.824 at 77°F (Water=1)
Solubility in Water	Soluble
Partition coefficient n-octanol/water (Log Kow)	Not Measured
Auto-ignition temperature	+/- 750°F
Decomposition temperature	Not Measured
Viscosity (cSt)	Not Measured
Coefficient of Water/Oil Distribution	No Oil or Water Present
Sensitivity to Mechanical Impact	Insensitive at 550-inch pounds
Sensitivity to Static Discharge	Not Available



Photographic Solutions

Safety Data Sheet

PEC-12[®]

SDS Revision Date: 01/01/2024

9.2 Other information

No other relevant information.

10. Stability and Reactivity

10.1 Reactivity

Reactive on exposure to strong oxidizing agents. Flammable exposure to sparks and open flame.

10.2 Chemical Stability

Stable under normal circumstances.

10.3 Possibility of hazardous reactions

No data available.

10.4 Conditions to avoid

High temperatures and fires.

10.5 Incompatible materials

CBI#1 : This ingredient is incompatible and causes violent reactions or ignitions with the following substances: Acetylene Bromide, Platinum, Potassium tert-butoxide, Phosphorus III oxide, Sodium, and Disulfuryl DiFluoride (violent reaction when mixed at ambient temperatures).

CBI#2 : This ingredient is incompatible with Potassium tert-butoxide.

10.6 Hazardous decomposition products

Carbon dioxide, carbon monoxide

11. Toxicological Information

11.1 Acute toxicity

Exposure to solvent vapor concentrations from the component solvents in excess of the stated occupational exposure limits may result in adverse health effects such as mucous membrane and respiratory system irritation and adverse effects on the kidneys, liver and central nervous system. Symptoms include headache, nausea, dizziness, fatigue, muscular weakness, drowsiness and in extreme cases, loss of consciousness.

Repeated or prolonged contact with the preparation may cause removal of natural fat from the skin resulting in dryness, irritation and possible non-allergic contact dermatitis. Solvents may also be absorbed through the skin. Splashes of liquid in the eyes may cause irritation and soreness with possible reversible damage.

Ingredient	Oral LD50, mg/kg	Skin LD50, mg/kg	Inhalation Vapor LC50, mg/L/4hr	Inhalation Dust/Mist LC50, mg/L/4hr	Inhalation Gas LC50, ppm
Ethanol - (64-17-5)	7,060.00, Rat - Category: NA	20,000.00, Rabbit - Category: NA	124.70, Rat - Category: NA	No data available	No data available
N-Butyl Acetate - (123-86-4)	10,700.00, Rat - Category: NA	17,600.00, Rabbit - Category: NA	No data available	No data available	No data available

Note: When no route specific LD50 data is available for an acute toxin, the converted acute toxicity point estimate was used in the calculation of the product's ATE (Acute Toxicity Estimate).



Photographic Solutions

Safety Data Sheet

PEC-12®

SDS Revision Date: 01/01/2024

Classification	Category	Hazard Description
Acute toxicity (oral)	---	Not Applicable
Acute toxicity (dermal)	---	Not Applicable
Acute toxicity (inhalation)	---	Not Applicable
Skin corrosion/irritation	---	Not Applicable
Serious eye damage/irritation	---	Not Applicable
Respiratory sensitization	---	Not Applicable
Skin sensitization	---	Not Applicable
Germ cell mutagenicity	---	Not Applicable
Carcinogenicity	---	Not Applicable
Reproductive toxicity	---	Not Applicable
STOT-single exposure	3	May cause drowsiness or dizziness.
STOT-single exposure	---	Not Applicable
STOT-repeated exposure	---	Not Applicable
Aspiration hazard	---	Not Applicable

12. Ecological Information

12.1 Toxicity

Toxic to aquatic life

Aquatic Ecotoxicity

Ingredient	96 hr LC50 fish, mg/l	48 hr EC50 crustacea, mg/l	ErC50 algae, mg/l
Ethanol - (64-17-5)	42.00, Oncorhynchus mykiss	2.00, Daphnia magna	17.921 (96 hr), Ulva pertusa
N-Butyl Acetate - (123-86-4)	18.00, Pimephales promelas	32.00, Artemia salina	674.70 (72 hr), Scenedesmus subspicatus

12.2 Persistence and degradability

This summary is designed to provide assistance should an accidental spill occur during shipment and does not address discharges to sanitary sewers or publicly owned treatment facilities. This product is expected to have a high BOD (Biochemical Oxygen Demand) and a potential to cause oxygen depletion in aquatic systems. It has a low potential to affect aquatic organisms and a low potential to persist in the environment. When diluted with large volumes of water, this product is not expected to have a significant impact as it is readily biodegradable and is not expected to bioconcentrate.

12.3 Bioaccumulative potential

Product is readily biodegradable and is not expected to bioconcentrate.

12.4 Mobility in soil

No data available

12.5 Results of PB and vPvB assessment

This product contains no PBT/vPvB chemicals.

12.6 Other adverse effects

No data available



Photographic Solutions

Safety Data Sheet

PEC-12[®]

SDS Revision Date: 01/01/2024

13. Disposal Considerations

13.1 Waste treatment methods

Destroy by liquid incineration. Use absorbent material and deposit in toxic landfill in accordance with local, state, and federal regulations.

14. Transport Information

DOT : Not regulated. If packaged according to DOT and/or carrier's requirements for ground/surface transport for LIMITED QUANTITY

IATA : Consumer Commodity, ID8000
Class 9 Packing Instruction 910 (There is no Packing Group Designation)
For International air shipments only

IMDG : Regulated (UN1993)
Page # 3230
Flammable Liquid NOS & Marine Pollutant

This product may be shipped via surface (ground) services if properly packaged and marked as a LIMITED QUANTITY. Consult carrier regulations for packaging requirements and suitability of mailing of LTD QTY materials.

15. Regulatory Information

Regulatory Overview The regulatory data in Section 15 is not intended to be all-inclusive, only selected regulations are represented.

Toxic Substance Control Act (TSCA) All components of this material are either listed or exempt from listing on the TSCA Inventory.

WHMIS Classification B2

US EPA Tier 2 Hazards:

Fire	Yes
Sudden Release of Pressure	No
Reactive	No
Immediate (Acute)	Yes
Delayed (Chronic)	No

EPCRA 311/312 Chemicals and RQs (lbs):

N-Butyl Acetate (5,000.00)

EPCRA 302 Extremely Hazardous:

To the best of our knowledge, there are no chemicals at levels which require reporting under this statute.

EPCRA 313 Toxic Chemicals:

To the best of our knowledge, there are no chemicals at levels which require reporting under this statute.

Proposition 65 - Carcinogens (>0.0%):

To the best of our knowledge, there are no chemicals at levels which require reporting under this statute.

Proposition 65 - Developmental Toxins (>0.0%):

To the best of our knowledge, there are no chemicals at levels which require reporting under this statute.



Photographic Solutions

Safety Data Sheet

PEC-12[®]

SDS Revision Date: 01/01/2024

Proposition 65 - Female Repro Toxins (>0.0%):

To the best of our knowledge, there are no chemicals at levels which require reporting under this statute.

Proposition 65 - Male Repro Toxins (>0.0%):

To the best of our knowledge, there are no chemicals at levels which require reporting under this statute.

New Jersey RTK Substances (>1%):

Ethanol

N-Butyl Acetate

Pennsylvania RTK Substances (>1%):

Ethanol

N-Butyl Acetate

16. Other Information

The information and recommendations contained herein are based upon data believed to be correct. However, no guarantee or warranty of any kind, expressed or implied, is made with respect to the information contained herein. We accept no responsibility and disclaim all liability for any harmful effects that may be caused by exposure to our products. Customers/users of this product must comply with all applicable health and safety laws, regulations, and orders.

The full text of the phrases appearing in section 3 is:

H225 Highly flammable liquid and vapor.

H226 Flammable liquid and vapor.

H336 May cause drowsiness and dizziness.

This is the first version in the GHS SDS format. Listings of changes from previous versions in other formats are not applicable.

This product is sold for professional photographic use only. It is not to be used or sold for personal, family or household use. The manufacturer can assume no liability if product is used in any manner inconsistent with its labelling or intent.

The information accumulated herein is believed to be accurate but is not warranted to be, whether originating with the company or not. Recipients are advised to confirm in advance of need that the information is current applicable and suitable to their circumstances.

****End of Document****